

GAIA

► www.bianchivending.com

USER INTERFACE

- . SELECTION PANEL WITH 8 BACKLIGHTED BUTTONS THAT CAN BE SET EITHER AS DIRECT SELECTIONS OR PRE-SELECTIONS.
- . THE FRONT PANEL OFFERS EXCELLENT BRANDING OPPORTUNITIES
- . 32 DIGIT ALPHANUMERIC DISPLAY.
- . 170 MM HIGH DELIVERY AREA WITH LIGHTING POSSIBILITY ABLE TO ACCOMMODATE BOTH SMALL ESPRESSO CUPS (WITH PIVOTING ESPRESSO CUP HOLDER), BIG CUPS, MUG OR A JUG.



GAIA
WITH COIN INTRODUCTION KIT



TECHNOLOGY



LED, LOW VOLTAGE
LIGHTING



PATENTED
ESPRESSO GROUP

A DISPENSER WITH HIGH PERFORMANCES
AND LOW INVESTMENT.

GAIA, automatic hot beverage machine, available both in espresso coffee from beans and instant beverages versions.



GAIA SPECIFICATIONS

ELECTRICAL SUPPLY

230Vac, 50Hz (CE compliance)
220-230Vac, 50Hz (IEC/CB compliance)

INTERNAL ELECTRICAL SUPPLY


All the electrical components are supplied at 24 Vdc, with the exception of the heating elements and of the pump that are powered by the mains voltage.

POWER SUPPLY

1.80 kW single boiler espresso version
1.80 kW alternating double boiler espresso version
2.80 kW double boiler espresso version


WATER SUPPLY

Fitting connection = 3/4"
Water pressure = 0.5 – 6.5 bar



GAIA ESPRESSO

1. COFFEE
2. CHOCOLATE
3. MILK



GAIA INSTANT

1. COFFEE
2. CHOCOLATE
3. MILK

VERSIONS GAIA	E2S ESPRESSO SINGLE BOILER*	E2S ESPRESSO DOUBLE BOILER*	I3S INSTANT*	I4S INSTANT*
COFFEE BEANS	1	1	-	-
INSTANT CANISTERS	2	2	3	4
DIMENSIONS	H 650 mm x W 310 mm x D 450 mm WEIGHT 25 kg			
CABINET	H 900 mm x W 310 mm x D 450 mm			

* all versions are available with water system supply or with autonomous tank

FEATURES

- All versions are available with water system supply or with autonomous tank.
- Water tank filling on the top the door and front lock for the functional closing of the machine.
- Mixers are extractable to make maintenance operations easier.
- Autonomous tank: 3.6 litres of water available placed behind the product canisters and possibility to fill with door closed.
- Liquid waste tray: 1 litre, easily extractable, with visible signal for maximum water level.
- Coffee waste tray: 60 pods with automatic block of the machine at reaching of maximum coffee waste level.

PRODUCT CAPACITY

	single canister	double canister
Coffee beans	0.80 kg (14 lt)	-
Instant coffee	0.35 kg (23 lt)	0.70 kg (46 lt)
Milk	0.55 kg (1.75 lt)	1.40 kg (3.5 lt)
Chocolate	1.30 kg (1.75 lt)	3.00 kg (3.5 lt)

ACCESSORIES KIT

- Base cabinet.
- Water system supply kit.
- RS232 module.
- Visual Smart Programmer Speed that allows the upload of the firmware and settings and the download of the settings and audit without a PC.
- Cup stations lighting kit through by software.
- Front panel pre-setted for validator assembly is available.

ENVIRONMENT

- Backlighted door and keypad with led to reduce energy consumption and with a lifetime greater than neon.
- In compliance with ROHS and WEEE.



Bianchi Vending Group • info@bianchivending.com
Corso Africa 9, 24040 Zingonia di Verdellino, Bergamo, Italia tel. +39.035.45.02.111, fax. +39.035.883.304

Specifications and technical information given are indicative and may be subject to change without prior notice. ZD-GAIA-ED12/2012/EN